# Optocoupler, Phototransistor Output, no Base Connection







## FEATURES

- Isolation test voltage, 5000 $V_{RMS}$
- No base terminal connection for improved common mode interface immunity
- Long term stability
- Industry standard dual-in-line package
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912

Pb-free
e3
RoHS COMPLIANT

## DESCRIPTION

The CNY17F is an optocoupler consisting of a gallium arsenide infrared emitting diode optically coupled to a silicon planar phototransistor detector in a plastic plug-in DIP-6 package.

The coupling device is suitable for signal transmission between two electrically separated circuits. The potential difference between the circuits to be coupled is not allowed to exceed the maximum permissible reference voltages.

In contrast to the CNY17 series, the base terminal of the F type is not conected, resulting in a substantially improved common-mode interference immunity.

## AGENCY APPROVALS

Safety application model number covering all products in this datasheet is CNY17F. This model number should be used when consulting safety agency documents.

- UL file no. E52744
- cUL tested to CSA 22.2 bulletin 5A
- DIN EN 60747-5-5 (VDE 0884-5), available with option 1
- BSI: EN 60065, EN 60950-1
- FIMKO EN60950
- CQC GB8898-2011

## ORDERING INFORMATION







| AGENCY CERTIFIED/PACKAGE | CTR (%) | | | |
|---|---|---|---|---|
| **UL, cUL, BSI, FIMKO** | **40 to 80** | **63 to 125** | **100 to 200** | **160 to 320** |
| DIP-6 | CNY17F-1 | CNY17F-2 | CNY17F-3 | CNY17F-4 |
| DIP-6, 400 mil, option 6 | CNY17F-1X006 | CNY17F-2X006 | CNY17F-3X006 | CNY17F-4X006 |
| SMD-6, option 7 | CNY17F-1X007 (1) | CNY17F-2X007T (1) | CNY17F-3X007T (1) | CNY17F-4X007T (1) |
| SMD-6, option 9 | CNY17F-1X009T (1) | CNY17F-2X009T (1) | CNY17F-3X009T (1) | CNY17F-4X009T (1) |
| **VDE, UL, cUL, BSI, FIMKO** | **40 to 80** | **63 to 125** | **100 to 200** | **160 to 320** |
| DIP-6 | CNY17F-1X001 | CNY17F-2X001 | CNY17F-3X001 | CNY17F-4X001 |
| DIP-6, 400 mil, option 6 | CNY17F-1X016 | CNY17F-2X016 | CNY17F-3X016 | CNY17F-4X016 |
| SMD-6, option 7 | CNY17F-1X017 (1) | CNY17F-2X017 (1) | CNY17F-3X017 (1) | CNY17F-4X017 (1) |
| SMD-6, option 9 | CNY17F-1X019 | CNY17F-2X019 (1) | CNY17F-3X019 (1) | - |

**Notes**

- Additional options may be possible, please contact sales office.

(1) Also available in tubes; do not put T on end.


For technical questions, contact: optocoupleranswers@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| **ABSOLUTE MAXIMUM RATINGS** ($T_{amb}$ = 25 °C, unless otherwise specified) | | | | |
|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITION** | **SYMBOL** | **VALUE** | **UNIT** |
| **INPUT** | | | | |
| Reverse voltage | | $V_R$ | 6 | V |
| DC forward current | | $I_F$ | 60 | mA |
| Surge forward current | t ≤ 10 µs | $I_{FSM}$ | 2.5 | A |
| Power dissipation | | $P_{diss}$ | 100 | mW |
| **OUTPUT** | | | | |
| Collector emitter breakdown voltage | | $BV_{CEO}$ | 70 | V |
| Collector current | | $I_C$ | 50 | mA |
| Collector peak current | $t_p/T$ = 0.5, $t_p$ ≤ 10 ms | $I_{CM}$ | 100 | mA |
| Output power dissipation | | $P_{diss}$ | 150 | mW |
| **COUPLER** | | | | |
| Isolation test voltage between emitter and detector | t = 1 min | $V_{ISO}$ | 5000 | $V_{RMS}$ |
| Storage temperature range | | $T_{stg}$ | -55 to +150 | °C |
| Ambient temperature range | | $T_{amb}$ | -55 to +110 | °C |
| Junction temperature | | $T_j$ | 100 | °C |
| Soldering temperature [(1)] | 2 mm from case, ≤ 10 s | $T_{sld}$ | 260 | °C |
| Total power dissipation | | $P_{diss}$ | 250 | mW |

**Notes**

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.

(1) Refer to reflow profile for soldering conditions for surface mounted parts (SMD). Refer to wave profile for soldering conditions for through hole parts (DIP).




Fig. 1 - Total Power Dissipation vs. Ambient Temperature

| **ELECTRICAL CHARACTERISTICS** ($T_{amb}$ = 25 °C, unless otherwise specified) | | | | | | | |
|---|---|---|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITION** | **PART** | **SYMBOL** | **MIN.** | **TYP.** | **MAX.** | **UNIT** |
| **INPUT** | | | | | | | |
| Forward voltage | $I_F$ = 60 mA | | $V_F$ | | 1.39 | 1.65 | V |
| Breakdown voltage | $I_R$ = 10 µA | | $V_{BR}$ | 6 | | | V |
| Reverse current | $V_R$ = 6 V | | $I_R$ | | 0.01 | 10 | µA |
| Capacitance | $V_R$ = 0 V, f = 1 MHz | | $C_O$ | | 25 | | pF |
| **OUTPUT** | | | | | | | |
| Collector emitter capacitance | $V_{CE}$ = 5 V, f = 1 MHz | | $C_{CE}$ | | 5.2 | | pF |
| Base collector capacitance | $V_{CE}$ = 5 V, f = 1 MHz | | $C_{BC}$ | | 6.5 | | pF |
| Emitter base capacitance | $V_{CE}$ = 5 V, f = 1 MHz | | $C_{EB}$ | | 7.5 | | pF |


For technical questions, contact: optocoupleranswers@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| **ELECTRICAL CHARACTERISTICS** ($T_{amb}$ = 25 °C, unless otherwise specified) | | | | | | | |
|---|---|---|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITION** | **PART** | **SYMBOL** | **MIN.** | **TYP.** | **MAX.** | **UNIT** |
| **COUPLER** | | | | | | | |
| Collector emitter, saturation voltage | $I_F$ = 10 mA, $I_C$ = 2.5 mA | | $V_{CEsat}$ | | 0.25 | 0.4 | V |
| Coupling capacitance | | | $C_C$ | | 0.6 | | pF |
| Collector emitter, leakage current | $V_{CE}$ = 10 V | CNY17F-1 | $I_{CEO}$ | | 2 | 50 | nA |
| | | CNY17F-2 | $I_{CEO}$ | | 2 | 50 | nA |
| | | CNY17F-3 | $I_{CEO}$ | | 5 | 100 | nA |
| | | CNY17F-4 | $I_{CEO}$ | | 5 | 100 | nA |

**Note**

- Minimum and maximum values were tested requierements. Typical values are characteristics of the device and are the result of engineering evaluations. Typical values are for information only and are not part of the testing requirements.

| **CURRENT TRANSFER RATIO** ($T_{amb}$ = 25 °C, unless otherwise specified) | | | | | | | |
|---|---|---|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITION** | **PART** | **SYMBOL** | **MIN.** | **TYP.** | **MAX.** | **UNIT** |
| $I_C/I_F$ | $I_F$ = 10 mA | CNY17F-1 | CTR | 40 | | 80 | % |
| | | CNY17F-2 | CTR | 63 | | 125 | % |
| | | CNY17F-3 | CTR | 100 | | 200 | % |
| | | CNY17F-4 | CTR | 160 | | 320 | % |
| | $I_F$ = 1 mA | CNY17F-1 | CTR | 13 | 30 | | % |
| | | CNY17F-2 | CTR | 22 | 45 | | % |
| | | CNY17F-3 | CTR | 34 | 70 | | % |
| | | CNY17F-4 | CTR | 56 | 90 | | % |

**Note**

- Current transfer ratio $I_C/I_F$ at $V_{CE}$ = 5 V, 25 °C and collector emitter leakage current by dash number.

| **SWITCHING CHARACTERISTICS** ($T_{amb}$ = 25 °C, unless otherwise specified) | | | | | | | |
|---|---|---|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITION** | **PART** | **SYMBOL** | **MIN.** | **TYP.** | **MAX.** | **UNIT** |
| **LINEAR OPERATION** (without saturation) | | | | | | | |
| Turn-on time | $I_F$ = 10 mA, $V_{CC}$ = 5 V, $R_L$ = 75 Ω | | $t_{on}$ | | 3 | | µs |
| Rise time | $I_F$ = 10 mA, $V_{CC}$ = 5 V, $R_L$ = 75 Ω | | $t_r$ | | 2 | | µs |
| Turn-off time | $I_F$ = 10 mA, $V_{CC}$ = 5 V, $R_L$ = 75 Ω | | $t_{off}$ | | 2.3 | | µs |
| Fall time | $I_F$ = 10 mA, $V_{CC}$ = 5 V, $R_L$ = 75 Ω | | $t_f$ | | 2 | | µs |
| Cut-off frequency | $I_F$ = 10 mA, $V_{CC}$ = 5 V, $R_L$ = 75 Ω | | $f_{CO}$ | | 110 | | kHz |
| **SWITCHING OPERATION** (with saturation) | | | | | | | |
| Turn-on time | $I_F$ = 20 mA | CNY17F-1 | $t_{on}$ | | 3 | | µs |
| | $I_F$ = 10 mA | CNY17F-2 | $t_{on}$ | | 4.2 | | µs |
| | | CNY17F-3 | $t_{on}$ | | 4.2 | | µs |
| | $I_F$ = 5 mA | CNY17F-4 | $t_{on}$ | | 6 | | µs |
| Rise time | $I_F$ = 20 mA | CNY17F-1 | $t_r$ | | 2 | | µs |
| | $I_F$ = 10 mA | CNY17F-2 | $t_r$ | | 3 | | µs |
| | | CNY17F-3 | $t_r$ | | 3 | | µs |
| | $I_F$ = 5 mA | CNY17F-4 | $t_r$ | | 4.6 | | µs |
| Turn-off time | $I_F$ = 20 mA | CNY17F-1 | $t_{off}$ | | 18 | | µs |
| | $I_F$ = 10 mA | CNY17F-2 | $t_{off}$ | | 23 | | µs |
| | | CNY17F-3 | $t_{off}$ | | 23 | | µs |
| | $I_F$ = 5 mA | CNY17F-4 | $t_{off}$ | | 25 | | µs |
| Fall time | $I_F$ = 20 mA | CNY17F-1 | $t_f$ | | 11 | | µs |
| | $I_F$ = 10 mA | CNY17F-2 | $t_f$ | | 14 | | µs |
| | | CNY17F-3 | $t_f$ | | 14 | | µs |
| | $I_F$ = 5 mA | CNY17F-4 | $t_f$ | | 15 | | µs |


For technical questions, contact: optocoupleranswers@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000




Fig. 2 - Test Circuit, Non-Saturated Operation




Fig. 3 - Test Circuit, Saturated Operation




Fig. 4 - Switching Times

| SAFETY AND INSULATION RATINGS | | | | |
|---|---|---|---|---|
| **PARAMETER** | | **SYMBOL** | **VALUE** | **UNIT** |
| **MAXIMUM SAFETY RATINGS** | | | | |
| Output safety power | | $P_{SO}$ | 700 | mW |
| Input safety current | | $I_{SI}$ | 400 | mA |
| Safety temperature | | $T_{SI}$ | 175 | °C |
| Comparative tracking index | | CTI | 175 | |
| **INSULATION RATED PARAMETERS** | | | | |
| Maximum withstanding isolation voltage | | $V_{ISO}$ | 5000 | $V_{RMS}$ |
| Maximum transient isolation voltage | | $V_{IOTM}$ | 8000 | $V_{peak}$ |
| Maximum repetitive peak isolation voltage | | $V_{IORM}$ | 890 | $V_{peak}$ |
| Insulation resistance | $T_{amb}$ = 25 °C, $V_{DC}$ = 500 V | $R_{IO}$ | $\geq 10^{12}$ | Ω |
| Isolation resistance | $T_{amb}$ = 100 °C, $V_{DC}$ = 500 V | $R_{IO}$ | $\geq 10^{11}$ | Ω |
| Climatic classification (according to IEC 68 part 1) | | | 55/115/21 | |
| Environment (pollution degree in accordance to DIN VDE 0109) | | | 2 | |
| Creepage distance | Standard DIP-4 | | ≥ 7 | mm |
| | SMD | | ≥ 7 | mm |
| Clearance distance | Standard DIP-4 | | ≥ 8 | mm |
| | SMD | | ≥ 8 | mm |
| Insulation thickness | | DTI | ≥ 0.4 | mm |

**Note**

- As per DIN EN 60747-5-5, § 7.4.3.8.2, this optocoupler is suitable for “safe electrical insulation” only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits.


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

**TYPICAL CHARACTERISTICS** ($T_{amb}$ = 25 °C, unless otherwise specified)




Fig. 5 - Forward Voltage vs. Forward Current




Fig. 8 - Leakage Current vs. Ambient Temperature




Fig. 6 - Collector Current vs. Collector Emitter Voltage (NS)




Fig. 9 - Normalized CTR (NS) vs. Ambient Temperature




Fig. 7 - Collector Current vs. Collector Emitter Voltage (sat)




Fig. 10 - Normalized CTR (sat) vs. Ambient Temperature


For technical questions, contact: optocoupleranswers@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000




Fig. 11 - Normalized CTR (NS) vs. Forward Current




Fig. 14 - CTR -3 dB Frequency vs. Collector Current




Fig. 12 - Normalized CTR (sat) vs. Forward Current




Fig. 15 - Switching Time vs. Load Resistance




Fig. 13 - CTR Frequency vs. Phase Angle


For technical questions, contact: optocoupleranswers@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

**PACKAGE DIMENSIONS** in millimeters




**PACKAGE MARKING** (Example of CNY17F-2x017T)




**Notes**

- VDE logo is only marked on option 1 parts. Option information is not marked on the part.
- Tape and reel suffix (T) is not part of the package marking.


For technical questions, contact: optocoupleranswers@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## TUBE AND TAPE INFORMATION

| DEVICES PER TUBE | | | |
|---|---|---|---|
| TYPE | UNITS/TUBE | TUBES/BOX | UNITS/BOX |
| DIP-6 | 50 | 40 | 2000 |




Fig. 16 - Tape and Reel Drawing, 1000 Units per Reel


For technical questions, contact: optocoupleranswers@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

# Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

***© 2023 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED***